

PALLET STACKERS

WS10 | WSX12/14 | WSXD20 | SX12/16 | PSX16



CLARK

CURR

-

-

Eres

CLARK PB

-

Long Operating Times Powerful Performance High Degree of Safety

Curles.

191615

EAND .

(LINE)

-

2000

10



PALLET STACKERS

Electric High-Lift Trucks Robust and Powerful

With CLARK high-lift pallet trucks with load capacities from 1,000 to 2,000 kg, you always have the organisation of your ware-house under control – whether in industry, trade or logistics. Even through the narrowest of aisles you can move up to two tons effort-lessly with these compact and maneuverable

pallet trucks. CLARK high lift trucks also prove their worth when loading and unloading vehicles. The sturdy CLARK mast of the electric high-lift trucks allows high residual capacities even at high lift heights. Thanks to the compact dimensions of the pedestrian stackers, safe handling is possible without any problems even in confined spaces. Do you need a pedestrian pallet truck or, for longer distances, a pallet truck with an operator platform? No problem: CLARK offers the right electric pedestrian pallet truck model for almost every requirement.



PALLET STACKERS WS10 | WS10M

CLARK THE FORKLIFT

Our entry-level models – for all those who want to handle simple tasks without any effort.



STANDARD-MAST

MONO-MAST

Ideal for Light Applications or as a Mobile Working Table

The WS10(M) is the entry-level model in our range of high lift trucks. Ideal for transport over short distances or as a mobile work table.

Compact Design

The compact trucks have a small length to the face of forks. This makes them very flexible and easy to maneuver even in confined spaces.

Integrated Chargers

With maintenance-free monobloc batteries and a built-in charger, the batteries can be recharged at any 230-volt socket.

Technical data: Electric Stacker WS10 | WS10M | WS10



Load capacity: 1000 kg



Lift height: WS10M max. 1950 mm WS10 max. 3300 mm



Drive speed: max. 4 km/h



Drive motor rating: 0,65 kW



Battery capacity: 24 V / 72 Ah

PALLET STACKERS WSX12/14 | WSXD20

Thanks to the AC technology and the CLARK Speed Control System (CSC), you can optimize your material handling flow with the WSX12 / 14 and WSXD20 stacker trucks.



For Medium-Intensity Applications and as Multifunctional Vehicle

The WSX12/14 and WSXD20 are suitable for industrial applications. They prove their worth wherever goods have to be transported over short distances.

CLARK Speed Control (CSC)

The Speed Control System is made for easier maneuvering in confined working areas. If the tiller is close to the chassis the maximum driving speed is automatically reduced.

Multi-Purpose Vehicle

The WSXD20 combines the features of a of a low and high lift truck in one unit. Doubledecker transport of goods is possible with this unit. This means two Euro pallets can be transported at the same time.

Technical data: Electric Stacker WSX12/14 | WSXD20



WSX14 1400 kg



<u>////.</u>

Load capacity WSXD20: Only initial-lift 2000 kg Only Mast lift 1200 kg Double-decker 1000 kg



Lift height: WSX12/14 max. 4800 mm WSD20 max. 3900 mm



Drive speed: max. 6 km/h



Drive motor

rating:

1,1 kW

I	

Battery capacity: 24 V / max. 225 Ah

PALLET STACKERS SX12/16



The robust masts of the SX-Series ensure a long service life and high performance. In addition a large number of options make sure that the SX-Series can be optimized to

match your requirements.



Powerful Stacker Trucks for Demanding Applications

The robust design of every component in the SX-Series guarantees durability and performance.

Proportional Hydraulic System

The motor-controlled proportional hydraulic system enables precise positioning of loads and increases the safety during application. Additionally the mast has a damping system as a standard.

Safety and Ergonomics

The centrally mounted tiller and the good visibility of the fork tips guarantee ergonomic and safe operation.

Technical data: Electric Stacker SX12/16





Load capacity: SX12 1200 kg



Load capacity: SX16 1600 kg



Lift height: max. 5210 mm



Drive speed: max. 6 km/h



Drive motor

rating:

1,2 kW



Battery capacity: 24 V / max. 375 Ah

You have the choice: For crossing ramps or obstacles, an initial lift is available as an optional feature. The initial lift also enables double-decker operation and thus two loads can be easily transported at the same time, or would you prefer a truck with a driver's platform? Or with both options?



Customisable Modifications

Due to the modular design of the SX-Series, the initial lift and platform version can be added either individually or together to the basic unit.

Keyless Activation via PIN-Code

When using the PIN-Code system, an automatic truck shut-down can be programmed. In addition, individual driving characteristics can be defined for different users.

Initial Lift for More Ground Clearance

With the aid of an additional lifting mechanism, the support arms and the battery compartment are raised, e.g. to overcome small bumps. The simultaneous lifting of two loads is also possible.

Battery capacity of up to 375 Ah

There are three different battery compartments available, as well as an optional side battery removal system. This makes it possible to provide exactly the battery power that is needed.

Foldable Driver's Platform

The foldable operator platform is ideal for medium-long distances. In this way, the maneuverability of a pedestrian vehicle is combined with the comfort of a ride-on vehicle.

Protective grille or plexiglass

In order to prevent reaching through the lift mast, two options are available: a plexiglass screen for best visibility or a protective grille that is easy to clean.



Productivity and ergonomics for heavy-duty operation and lift heights up to 5800 mm, also available in a Lithium-Ion-Version.



Pure Productivity

The PSX16 is perfect for transporting goods over longer distances. The stocking and unloading in higher racking levels is also possible.

Power Steering as Standard Equipment

For longer distances and long periods of use the standard power steering ensures fatigue-free operation.

Lithium-lon Technology available

The Lithium-Ion-Version guarantees high availability thanks to short recharging times. Time-consuming battery changes can thus be avoided.

Technical data: Electric Stacker PSX16



Load capacity: 1600 kg



Lift height: 5800 mm



Drive speed: max. 6 km/h



Drive motor rating: 1,6 kW



Battery capacity:

Lead acid version

max. 375 Ah

_

Battery capacity: Lithium-Ion-Version 205 Ah







 CLARK EUROPE cmbH
 Implementation

 Dr.Alfred-Horrhausen-Allee 33
 Implementation

 Ar228 Duisburg / Germany
 Implementation

 Info-europe@clarkmheu.com + www.clarkmheu.com
 Implementation